



A

NOTES:

1. ORIENT SOLAR PANEL TOWARDS SOUTHERN SKY FOR MAXIMUM SOLAR EXPOSURE
2. CONTROL CABINET HEIGHT MAY VARY.
3. SNAP LOCKS ARE PROVIDED, STANDARD 3/4" S/S BANDING IS RECOMMENDED
4. J-BOLTS NOT SHOWN



S:\BLINKERSIGNR&DTAPCO IN HOUSE ENGINEERING\DRAWINGS\SALES DRAWINGS (2TE-XXX)\NATIVE FORMAT (INVENTOR-SOLIDWORKS)

TOLERANCE UNLESS OTHERWISE SPECIFIED	
HOLE ϕ ± 0.003	
DEC.	MM INCH
X	± 2.540 ± 0.100
XX	± 0.762 ± 0.030
XXX	± 0.381 ± 0.015
XXXX	± 0.0127 ± 0.0005
ANGULAR $\pm 0.5^\circ$	

TITLE:
SOLAR TRIPLE BLINKER BEACON SYSTEM

DESIGNED BY:		SIZE	DWG. NO.
DRAWN BY:	A. KAVANAUGH	B	2TE-535
CHECKED BY:	M. SMITH		

MATERIAL		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5-2009
FINISH	VARIED	REFERENCE:

STORAGE SIZE:	
REV	WEIGHT:
A	
	SCALE: 1:26

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TAPCO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TAPCO IS PROHIBITED.

SHEET 1 OF 1