

AI-500-070 School Beacon Timer Switch and Cellular Modem

Overview

The AI-500-070 series provides a cost-effective, easy to integrate means of adding monitoring and control to School Beacons Flashers. It is designed for extreme temperature applications and has low power requirements, making it suitable for solar powered applications. The simple Integrated School Beacon Timer Switch and Cellular Modem can be retrofitted into existing School Beacon cabinets to upgrade the school beacons to the latest technology.

The unit provides an easy way to monitor the school beacons status and health such as AC power, battery backup, monitor beacon current, cabinet door open, local override control and temperature.

The unit works in conjunction with the Glance Platform, providing an cloud-based School Beacon solution. Simply connect the unit to your school beacons to add monitoring and control to your equipment. The unit allows you to remotely configure schedules for the school beacons from the Glance cloud based software.

Features

- ✓ Low cost Internet connectivity solution
- ✓ Small form factor
- ✓ Low power consumption
- ✓ Compatible with Glance platform
- ✓ GPS enabled for self-locating
- ✓ Monitor beacon lamps current to determine when a beacon has failed
- ✓ Remotely change schedule to multiple devices
- ✓ Ability to control secondary school beacons upstream
- ✓ Email & text messages when faults are detected
- ✓ Integral battery back-up for power fail reporting
- ✓ Local manual override switch



Call us today to get started at [678.830.2170](tel:678.830.2170) or email us at sales@appinfoinc.com!

Hardware Specification



AI-500-070

Connectivity

Cell Modem *	Yes
Ethernet Port (10/100Base-T)	Yes
RS-232 Port	Optional **

Industrial I/O

Analog Inputs	AC Power, Solar Batteries & Temperature
Digital Inputs	Beacon Status & Door Open Switch
Digital Outputs	2 X Beacon Circuits

Miscellaneous

Operating Systems	µC/OS-II
GPS	Yes
Operating Temperature	-40°C to 80°C
Humidity	5-95% non-condensing
Dimensions	8" x 5" x 2"
Input Voltage	10-30v DC, 120V AC
Real Time Clock	Yes
Flash Disk	Yes
Battery Backed Memory	Yes

Also suitable for...

Solar/battery powered	Yes
Lamp Monitoring	Yes
Scheduling	Yes

* Specify carrier at time of order

** Custom configurations available for volume orders

