

Ocean State Signal Co.

27 Thurber Blvd • Smithfield, RI 02917
 (401) 231-6780 • Fax: (401) 231-4390



SPECIFICATION SHEET

TITLE: Pedestrian Signal LED Modules

PART NO.: see below

LED Color/Type: Portland Orange ● /AllnGaP, Lunar White ○ /InGaN

Operating Temperature: -40°F to 165°F (-40°C to 74°C)

Total Harmonic Distortion (THD): < 20%

Operating Voltage: 80 - 135Vac


Turn-On/Turn-Off Time: < 75msec

Power Factor: > 0.90



Turn-Off Voltage: > 35Vac

Mechanical Dimensions [in(mm)]


CIL, CD Digit Height - 9"




CIL Series





CD Series




CD, WM, EH, HM Digit Height - 9"



CD Series



HM Series



Model Number	Description	Wattage Drawn	Standard
12 inch Countdown Pedestrian			
TP12N-CD	Countdown Digits - Portland Orange Countdown	7.5W	ITE PTC SI-LED Signal Modules - Aug 4, 2010 / ETL ¹
12 inch Pedestrian			
TP12B-EH	Full Symbol – Portland Orange Hand	6W	ITE PTC SI-LED Signal Modules - Aug 4, 2010 / ETL ¹
TP12H-HM	Overlay Full Symbol – Portland Orange Hand / Lunar White Man	Hand – 7W Man – 7W	ITE PTC SI-LED Signal Modules - Aug 4, 2010 / ETL ¹
16 inch Incandescent Look Dual Pedestrian Countdown			
TSL-PED-16-CIL-P1*	Full Symbol	Portland Orange Hand – 7.9W Lunar White Man – 6W Portland Orange Countdown – 5.3W	ITE PTC SI-LED Signal Modules - Aug 4, 2010/ETL ¹