

Supplied in lengths shown below, Pelco's vertical support tubing is made from high strength aluminum alloy. A unique shape and vinyl insert insures a complete weather proof wiring installation anywhere along the entire length of the tube.

The standard 46" tube will accommodate all signal combinations up to 3-Section 12". Tubes are also available in 58" and 74" lengths for 4 and 5-Section combinations.


ITEM	DESCRIPTION	PART NO.
①	<b>GUSSETED TUBE w/ VINYL INSERT:</b>	
	1½" x Length, Threaded One End .....	AB-2003
②	1½" x Length, Threaded Both Ends .....	AB-2007
	<b>GUSSETED TUBE ONLY:</b>	
③	1½" x Length, No Threads .....	AB-0300
④	1½" x Length, Threaded One End .....	AB-0306
⑤	1½" x Length, Threaded Both Ends .....	AB-0307
⑥	<b>ALUMINUM TUBE</b>	
	1½" x Length, No Threads .....	SE-0484

**Notes:**

1. Lengths up to 120" maximum are available upon request.
2. Please specify options when ordering.

OPTIONS
TUBE LENGTH: 23" for up to 1-sec 12"
37" for up to 2-sec 12" & 5-sec cluster
46" for up to 3-sec 12"
58" for up to 4-sec 12"
74" for up to 5-sec 12"
PAINT

**Concealed Wiring Installation**



Pelco's aluminum gusseted tubes allow wire entry at any point. vinyl insert conceals wiring from mast arm to signal head. Simply run wire through field-drilled hole in mast arm, through Astro-Brac, and into support tube. Hollow lower arm provides a channel for wire to be fed into signal head.